



5W40 excellent

Lubricare 5W40 excellent motor oil is a synthetic motor oil.

This is a full synthetic lubricant based on carefully selected very high quality base oils and high quality additives of the latest generation, specially designed to meet the strict requirements of manufacturers. This provides an excellent fluidity at low temperatures, a very low resistance when starting, an exceptional viscosity index and a very high thermal stability.

applications

A universal, special composed synthetic motor oil recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans for which the most modern specifications are required.

specification level or performance

- ACEA: A3/B4
- API: SN/CF
- MB: 226.5
- MB: 229.3
- BMW: LONGLIFE-01
- OPEL: GM-LL-B-025
- VW: 502 00
- VW: 505 00
- VW: 505 01
- RENAULT: RN 0700
- RENAULT: RN 0710
- Fiat 9.55535-M2
- PORSCHE: A40
- PSA: B71 2296

typical characteristics :

test		unit	average result
Density at 15°C		kg/l	0.853
Viscosity at -30°C		mPas	5740
Viscosity at 40°C		mm ² /s	90.20
Viscosity at 100°C		mm ² /s	15.00
Viscosity index			175
Flash point COC		°C	223
Pour point		°C	-42
TBN		mg KOH/g	10.50
Sulfated ash		massa %	1.33

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.