

Product description ECORA tyre mounting paste Black / white / yellow

ECORA tyre mounting paste physiologically safe and organic degradable!

Product description and instructions for use:

According to our application instructions, our ECORA tyre fitting WAX should be used Brush on the tyre beads, rim well and the inclined shoulder ring thin-walled to be spread. After the ECORA tyre fitting WAX has been consolidated, one forms thin separation layer between tyre and rim. This interface prevents the tyre from sticking to the rim and at the same time protects the tyre rim Rust attack and neutralizes existing rust spots.

If our application instructions are observed, the technically perfect fit of the Guaranteed tyre on the rim. We have according to the regulations our paste is set to dry quickly to avoid the risk of tyre wandering exclude on the rim.

Characteristics:

Facilitates assembly work and supports later disassembly because the tyre is not on the rim sticks. Low effort and time required due to high gliding properties beneficial to the tyre material. Prevents cracks and age problems and is very economical in use and quick drying. The ECORA tyre mounting WAX is for the installation of all types of tyres, especially suitable for run-flat tyres.

Application:

apply thinly to the tyre beads with a brush or sponge, for truck and EM tyres also coat the rim well and the inclined shoulder ring. As a result, the tyre slips easily and without damage to the rim. ECORA -Reifen-Montier-Wax guarantees the technically perfect fit of the tyre the rim - as a prerequisite for precise balancing - and facilitates the later Disassembly.

Technical specifications:

Color: white, black or yellow

Odor: neutral

Consistency: firm (WAX)

Processing temperature: - 15 ° C to 50 ° C