SAFETY DATA SHEET DF CORP LTD

Section 1. Identification of the substance/mixture and of the company/undertaking

1.1 Product Identifier

Product Form: Mixture

Product Name: Air Freshener Aerosol 750ml/400ml/270ml/100ml

Product No: Fleur – PN299897

1.2 Relevant identified uses of the substances of mixture and uses advised against

1.2.1 Relevant Identified uses

Air Freshener for general public use

1.2.2 Uses advised against

No additional information available

1.3 Details of the supplier of the safety data sheet

Company name: DF Corp Ltd

Company address: Unit 16 Clayton Court

Welcomb street Openshaw Manchester

M11 2NB

hello@designerfragrances.eu

1.4 Emergency telephone number

+44 (0) 161 2237655

Mon - Fri 0900-1700

Section 2. Hazards Identification

2.1 Classification of the substance or mixture

Classification according to (EC) 1272/2008 [CLP]

Aerosol Category 1 H222;H229

Serious eye damage/eye irritation Category 2 H319

The full text for all Hazard statements are displayed in Section 16.

Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol

2.2 Label elements

Label in accordance with (EC) 1272/2008 [CLP]

Hazard pictograms (CLP)





GHS02 GHS07

Signal Word (CLP): Danger

Hazard Statements (CLP):

H222 Extremely Flammable Aerosol

H229 Pressurised container: May burst if heated

H319 Causes serious eye irritation

Precautionary Statements (CLP):

P102 Keep out of reach of children

P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

P211 Do not spray on an open flame or other ignition source
P251 Pressurized container: Do not pierce or burn even after use

P501 Dispose of contents/container in accordance with Local Regulations

Supplementary Precautionary Statements:

P273 Avoid release to the environment

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P370+378 In case of fire: Use carbon dioxide, dry chemical, foam for extinction.
P410+412 Protect from sunlight. Do not expose to temperatures exceeding

50°C/122°F.

2.3 Other hazards:

No additional information available

Sections 3. Composition / information on ingredients

3.1 Substance

Not applicable

3.2 Mixtures

Contains:

Name	CAS	EC	%	Classification for (CLP)
				1272/2008
Petroleum Gases Liquified	68476-85-7	270-704-2	60-80%	Flam Gas 1-H220
Ethyl alcohol	64-17-5	200-578-6	<20%	Flam Liq 2-H225
				Eye Irrit 2:H319 (SCL
				≥50%)

The full text for Hazard and Precautionary statements are listed in Section 16.

Section 4. First aid measures

4.1 First aid measures

General information

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

Inhalation

Move the exposed person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep the affected person warm and at rest. Get prompt medical attention.

Ingestion

DO NOT induce vomiting. Get medical attention immediately

Skin contact

Wash the skin immediately with soap and water. Promptly remove clothing if soaked through and wash as above. Get medical attention if any discomfort continues.

Eye Contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms/injuries: Not expected to present a significant hazard under anticipated conditions of

normal use

Symptoms/injuries after inhalation: Not expected to present a significant inhalation hazard under anticipated

conditions of normal use. May cause slight irritation.

Symptoms/injuries after skin contact: Not expected to present a significant skin hazard under anticipated

conditions of normal use. May cause slight irritation.

Symptoms/injuries after eye contact: Causes eye irritation.

Symptoms/injuries after ingestion: Not expected to present a significant ingestion hazard under anticipated

conditions of normal use. May cause a light irritation of the linings of the

mouth, throat, and gastrointestinal tract.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically

Section 5: Firefighting measures

5.1 Extinguishing media

Suitable media: Carbon dioxide, Dry chemical, Foam.

5.2 Special hazards arising from the substance or mixture.

Fire hazard: Extremely flammable aerosol

Reactivity in case of fire: Not known

Hazardous decomposition

Products in case of fire: Toxic fumes may be released

5.3 Advice for fire fighters:

Precautionary measures fire: Stop leak if safe to do so

Firefighting instructions: Eliminate all ignition sources if safe to do so. Fight fire with normal

Precautions from a reasonable distance

Protection during firefighting: Do not attempt to take action without suitable protective equipment.

Self-contained breathing apparatus. Complete protective clothing.

Section 6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

General measures: Ensure adequate ventilation. Eliminate ignition sources. Avoid release into

The environment.

6.1.1 For non-emergency personnel

Protective equipment: Not required for normal conditions of use

Emergency procedure: Ventilate spillage area. Eliminate all ignition sources if safe to do so. Avoid contact

With skin and eyes

DF Corp Ltd REV 4.2 JUNE 2016

6.1.2 for emergency responders

Protective equipment: Do not attempt to take action without suitable protective equipment. For further

Information refer to section 8:"Exposure controls/personal protection". Avoid

Contact with skin and eyes.

Emergency procedure: Ventilate spillage area. Eliminate all ignition sources if safe to do so.

6.2 Environmental precautions:

Avoid release into the environment.

6.3 Methods and material for containment and cleaning up:

For containment: Not applicable

Methods for cleaning up: This material and its container must be disposed of in a safe way, as per

local regulations and legislation.

Other information: This material and its container must be disposed of as hazardous waste. Dispose of

in a safe way, as per local regulations and legislation.

6.4 Reference to other sections:

Also refer to sections 8 and 13.

Section 7. Handling and storage

7.1 Precautions for safe handling:

Additional hazards when

processed: Handle empty containers with care because residual vapours are flammable.

In use, may form flammable vapour-air mixture. Pressurized container: Do not

Pierce, or burn, even after use.

Precautions for safe handling: Keep away from heat, hot surfaces, sparks, open flames and other ignition

Sources. No smoking. Do not spray on to an open flame or other ignition Source. Pressurized container: do not pierce or burn, even after use.

Hygiene measures: Do not eat, drink or smoke when using this product.

7.2 Conditions for safe storage, including any incompatibilities.

Technical measures: Ensure adequate ventilation

Storage conditions: Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F

Store in a well ventilated place. Keep cool.

Incompatible products: Strong bases, strong acids. Oxidising agents. Incompatible materials: Sources of ignition. Heat sources. Direct sunlight.

Storage area: Store in a well ventilated place. Keep away from open flames, hot surfaces,

And sources of ignition.

Special rules on packaging: Keep only in original container.

7.3 Specific end use(s):

Air care products. Use in accordance with good manufacturing and industrial hygiene practises.

Section 8. Exposure controls/personal protection

8.1 Control Parameters

No additional information available.

8.2 Exposure controls

Workplace exposure limits:

Ingredient	CAS	EC	STD	TWA – 8 Hrs	STEL- 15 Min	Reference

Petroleum	6847	270-	WEL	1000 ppm	1250ppm	UK EH40 Dec
Gases	6-85-	704-2		1750 mg.m ³	2180 mg.m ³	2011
Liquefied	7					
Ethyl	64-	200-	WEL	1000 ppm		UK EH40 Dec
alcohol	17-5	578-6		1290 mg.m³		2011

Derived No Effect Levels (DNEL):

Petroleum Gases Liquified

Not applicable

Ethanol

DNEL for workers

Inhalation DNEL (short term, 1900 mg/m3 (irritation respiratory tract)

local)

Inhalation DNEL (long term, 950 mg/m3 (carcinogenicity)

systemic)

Dermal DNEL (long term, 343 mg/kg bw/day (repeated dose toxicity)

systemic)

DNEL for the general population

Inhalation DNEL (short term, 950 mg/m3 (irritation respiratory tract)

local)

Inhalation DNEL (long-term, 114 mg/m3 (carcinogenicity)

systemic)

Dermal DNEL (long-term, 206 mg/kg bw/day (repeated dose toxicity)

systemic)

Oral DNEL (long-term, 87 mg/kg bw/day (repeated dose toxicity)

systemic)

Predicted No Effect Concentration (PNEC):

Petroleum Gases Liquified

Exposure assessments have not been presented for the environment, therefore PNEC values not required

Ethanol

PNEC aqua (freshwater) 0,96 mg/L PNEC aqua (marine water) 0,79 mg/L PNEC aqua (intermittent 2,75 mg/L

releases):

PNEC sediment (freshwater): 3,6 mg/kg sediment dw PNEC sediment (marine water): 2,9 mg/kg sediment dw PNEC soil 0,63 mg/kg soil dw

PNEC STP (Sewage Treatment

Plant)

PNEC oral (food chain) 0,72 g/kg food

8.2 Exposure Controls

Engineering Measures

Distribution, Workplace and Household Settings: Ensure adequate ventilation

580 mg/L

Personal Protective Equipment

Eye Protection

Distribution, Workplace and Household Settings: No special protective equipment required

Hand Protection

Distribution, Workplace and Household Settings: No special protective equipment required

Skin and Body Protection

Distribution, Workplace and Household Settings: No special protective equipment required

Respiratory Protection

Distribution, Workplace and Household Settings: No special protective equipment required

Section 9. Physical and chemical properties

No data available

9.1 Information on basic physical and chemical properties

(a) Appearance Aerosol.

(b) Odour

c) Odour Threshold

(d) pH

No data available

(e) Melting point/freezing point

No data available

(f) Initial boiling point and boiling range

(g) Flash point

Estimated at -35°C

(h) Evaporation point

Distinctive fragrance

No data available

Setimated at -35°C

No data available

(i) Flammability (solid gas)(j) Upper/lower flammability

Or explosive limits

(k) Vapour pressure

(l) Vapour density

(m) Relative density

(n) Water solubility

No data available
No data available
No data available

(o) Partition coefficient

n-octanol/waterNo data available(p) Auto-ignition temperatureNo data available(q) Decomposition temperatureNo data available(r) ViscosityNo data available

(s) Explosive properties Pressurised contained. May burst if heated.

(t) Oxidising properties No data available.

9.2. Other information

Can pressure 70psi.

Section 10.Stability and reactivity

10.1 Reactivity:

Presents no significant reactivity hazard, by itself or in contact with water.

10.2 Chemical stability

Good stability under normal storage conditions.

10.3 Possibility of hazardous reactions:

Not expected under normal conditions of use.

10.4 Conditions to avoid:

Avoid contact with hot surfaces/heat. No flames; no sparks. Eliminate all sources of ignition

10.5 Incompatible materials:

Avoid contact with strong acids, alkalis or oxidising agents.

10.6 Hazardous decomposition products:

Not expected

Section 11. Toxicological information

11.1 Information on toxicological effects

This mixture has not been tested as a whole for health effects. The health effects have been calculated in accordance with methods given in regulation (EC) No 1272/2008.

Based upon the hazardous properties of the component substances, and their concentrations, this product has been assessed according to the calculation method of CLP, and found not to be classified for toxicological effects.

Acute Toxicity: Not classified

Ethyl Alcohol:

LD50 Oral - Rat 10,470 mg/kg LC50 Inhalation - Rat 30,000 mg/l - 4 h15,800 mg/kg LD50 DermaL - Rabbit Skin corrosion/Irritation Not classified Serious eye damage/eye irritation Not classified Repiratory or skin sensation Not classified Germ cell mutagenicity Not classified Carcinogenicity Not classified **Reproductive Toxicity** Not classified **Specific Target Organ Toxicity** Not classified **Aspiration hazard** Not classified

Potential adverse human health

Effects and symptomsBased on available data, the classification criteria are not met

Section 12. Ecological information

12.1 Toxicity:

Based upon the hazardous properties of the component substances, and their concentrations, this product has been assessed according to the calculation method of CLP, and found not to be classified for ecological effects.

Ethyl alcohol

Toxicity to fish LC55 – Primephales promelas (Fathead minnow) – 14,200 mg/l – 96 h

Toxicity to daphnia and other

Aquatic vertebrates LC50 - Ceriodaphnia dubia (Water flea) -5,012 mg/l - 48 hToxicity to algae EC50 - Chlorella vulgaris (Fresh water algae) -275 mg/l - 72 h

(OECD Test Guidelines 201)

Liquid petroleum gases

Physical properties indicate that petroleum gases will rapidly volatilise from the aquatic environment and that acute and chronic effects would not be observed in practice.

12.2 Persistence and degradability:

Ethyl alcohol

Result: 95% - Readily biodegradable

Liquid petroleum gases

Expected to be readily biodegradable. Oxidises rapidly by photo-chemical reactions in air

12.3 Bioaccumalative potential:

Ethyl alcohol

Due to the distribution coefficient n-octanol/water, accumulation in organisms is not expected.

Liquid petroleum gases

Not expected to bioaccumulate significantly

12.4 Mobility in soil:

Ethyl alcohol

No data available

Liquid petroleum gases

Because of their extreme volatility, air is the only environmental compartment that hydrocarbon gases will be found.

12.5 Results of PBT and vPvB assessment:

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

12.6 Other adverse effects:

No data available.

Section 13. Disposal considerations

13.1 Waste treatment methods:

Dispose of in accordance with local regulations. Avoid disposing into drainage systems and into the environment. Empty containers should be taken to an approved waste handling site for recycling or disposal according to Local Authority Regulations

Section 14. Transport information

14.1 U	N N	um	ber
--------	-----	----	-----

 UN No (ADR/RID/ADN)
 1950

 UN No (IMDG)
 1950

 UN NO (ICAO)
 1950

14.2 UN Proper Shipping Name

ADR/IMDG/AND/RID AEROSOLS

IATA Aerosols Flammable

14.3 Transport Hazard Class(es)

ADR/RID/ADN Class 2.1

ADR/RID/ADN Class Class 2: Gases **ADR Label No** 2.1 & 6.1 2.1 IATA **IMDG Class** 2.1 ICAO Class/Division 2.1 **ICAO Subsidiary Risk** 6.1 **ICAO TEC* No** 20GSF 2.1 Air Class **UK Road Class** 2.1 **Transport Labels** L.Q.



14.4 Packing Group

Not Applicable

14.5 Environmental Hazards

Dangerous for the environment No Marine pollutant No

Other information No supplementary information available

14.6 Special Precautions for user

Overland Transport

Classification Code (ADR): 5F

Special Provisions (ADR): 190,327,344,625

Limited Quantities (ADR): 11 Excepted Quantities (ADR): E0

DF Corp Ltd **REV 4.2 JUNE 2016** Packing Instructions (ADR): P207,LP02 Special Packing provisions (ADR): PP87, RR6, L2 Mixed Packing provisions (ADR): MP9 Transport Strategy (ADR): 2 Special provisions for carriage – Packages (ADT) V14 Special Provisions for carriage - Loading, unloading and handling (ADR): CV9, CV12 Special provisions for carriage – Operation (ADR): **S2 Tunnel Restriction Code:** D Transport by Sea Special Provisions (IMDG): 63,190,277,327,344,959 Limited Quantities (IMDG): SP277 Excepted Quantities (IMDG): F0 Packing Instructions (IMDG): P207,LP02 Special Packing provisions (IMDG): PP87,L2 EmS-No (Fire): F-D EmS-No (Spillage): S-U Stowage category (IMDG): None Stowage and Handling (IMDG): SW1,SW22 Segregation (IMDG): SG69 MFAG-No: 126 Air Transport PCA Excepted Quantities (IATA): E0 PCA Limited Quantities (IATA): Y203 PCA Limited Quantity max net quantity (IATA): 30KgG PCA Packing instructions (IATA): 203 PCA max net quantity (IATA): 75Kg CAO packing instructions (IATA): 203 CAO max net quantity (IATA): 150Kg A145,A167,A802 Special provisions (IATA): ERG Code (IATA): 10L **Inland Waterway Transport** Classification Code (ADN): 5F 190,327,344,625 Special Provisions (ADN): Limited Quantities (ADN): 1 L **Excepted Quantities (ADN):** F0 Equipment required (ADN): PP.EX.A Ventilation (ADN): VE01, VE04 Number of blue cones/lights (ADN): 1 Rail Transport Classification Code (RID): 5F Special Provisions (RID): 190,327,344,625 Limited Quantities (RID): 1L **Excepted Quantities (RID):** E0 P207,LP02 Packing Instructions (RID): Special Packing provisions (RID): PP87,RR6,L2 Mixed Packing provisions (RID): MP9 Transport Category (RID): 2 Special Provisions for carriage – Packages (RID): W14 Special Provisions for carriage – Loading, unloading

CW9, CW12

CE2

23

and handling (RID):

Colis Express (express parcels) (RID):

Hazard Identification No (RID):

14.7 Transport in bulk according to Annex II of MARPOL and the IBC code

Not applicable

Section 15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Labelling according to Regulation (EC) No 1272/2008

The chemicals (Hazard information and packaging for supply) regulations 2009 (S.I 2009 No. 716). Control of substances hazardous to health.

Approved code of practice.

Guidance notes

Workplace exposure limits EH40.

15.1.1 EU-Regulations

Contains no REACH substances with Annex XVII restrictions.

Contains no REACH Annex XIV substances.

15.1.2 National Regulations

No additional information available.

15.2 Chemicals safety assessment

A chemical safety assessment has not been carried out for this product.

Section 16. Other information

General Information:

This product should be used as directed. For further information consult the product data sheet or contact Technical Services.

Information sources:

This Safety Data Sheet was compiled using current safety information supplied by the distributor of raw materials.

Classification under regulation (EC) No 1272/2008

Flam Gac 1

Hazard statements in full

П220	extremely naminable gas.
H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H229	Pressurised container. May burst if heated
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H410	Very toxic to aquatic life with long lasting effects

Flammable Gas Category 1

Extramaly flammable gas

Abbreviations

riaiii Gas I	Figitifiable das Category 1
Flam Liq 2	Flammable Liquid Category 2
Eye Irrit 2	Eye Irritant category 2
Skin Irrit 2	Skin irritant category 2
Skin Sens 1	Skin sensitivity category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard Category 1
LD50	Lethal Dose 50%

DF Corp Ltd REV 4.2 JUNE 2016

LC50 Lethal Concentration 50%

OECD Organisation for Economic and Co-operative Development

PBT Persistent Bioaccumulative Toxicity vPvB Very Persistent Very Bioaccumulative

IMDG International Maritime Transport of Dangerous Goods

ICAO International Civil Aviation Organisation

ISSUE: REV 4.2 REVISION DATE: JUNE 2019

DISCLAIMER

The Information provided herein, especially recommendations for the usage and the application of this products, is provided in good faith, and no liability on the part of DF Corp Ltd is stated or implied. No employee of DF Corp Ltd has the authority to waive or alter in any way the content of this document.

Due to different materials used, as well as to varying working conditions, production techniques, and the requirements of the end users, all of which are beyond our control, we strongly recommend that thorough and extensive trials are carried out in order to test the suitability of our products with regard to the required processes and applications. This should also include an ageing test which should be applied to all substrates used.

It is also the responsibility of the purchaser and end user of this product to ensure that all appropriate actions necessary for the protection of the environment, and for the health and safety of their employees are observed.

This datasheet replaces all former versions