

## MOTIP V-Belt Spray

Ord.-no.: 090102

### Technical Information



Protect the v-belt of your car with MOTIP V-Belt spray to remedy and prevent slipping. Also suitable for other vehicles and machines. Spray with excellent adhesion to protect V-Belts and to remedy and prevent slipping. MOTIP V-Belt spray is dilatant (increases in volume and viscosity) and user-friendly and gives lasting protection. MOTIP V-Belt Spray delays the wear, conditions V-belts and is resistant to the weather.

#### Quality & properties

- Remedies and prevents slipping and creaking
- Excellent adhesion and lasting protection
- Dilatant
- Resistant to weather influences
- Delays the wear and conditions V-Belts
- Directed jetspray
- User-friendly

#### Physical & chemical data

- Base: Polyalphaolefine
- Colourname: Transparent
- Smell: characteristic
- Degree of gloss: mat, 10 ±2
- Surfaces: Vehicles, Machinery, Conveyer belts, Agricultural Machinery, Drill Presses, Concrete mixers, Lathes Lawn mower, Generators, Compressors, Forklift trucks Pumps, Milling machines
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Spray rate: 1,15
- Vapour pressure: 3500/20 bar
- Flash point: n.a.
- Relative density: 0.89 g/ml
- Storage stability: 10 years
- Content: 500 ML

#### How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The aerosol should have room temperature.
- Best processing temperature 10 to 25°C.
- Before use, shake the aerosol.
- Switch off the engine.
- Apply the V-Belt Spray in an equal, thin layer on the threads of the V-Belt and allow to take effect
- After evaporation of the solvent, the engine can be switched on.

#### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

#### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

#### Marking/Labeling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +31 (0) 561 69 44 55 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of November 24, 2021 – This release replaces all eventually earlier issued versions.

