

MOTIP White Grease

Ord.-no.: 090204, 290204

Technical Information



Loosen stuck parts with MOTIP White Grease and make sure that hinges, bearings, springs, etc. run smoothly again. Spray Grease has excellent adhesion and high viscosity to lubricate mechanical parts of metal or plastic. White grease has outstanding mechanical and thermal stability and is resistant to the weather and weak acids and bases. White grease is water-repellent and pH neutral. White grease contains PTFE (polytetrafluorethen) and prevents wear and sticking. MOTIP White Grease is resistant to temperatures of - 30°C up to + 160°C.

Quality & properties

- Outstanding mechanical and thermal stability
- High viscosity
- Contains PTFE (polytetrafluorethen)
- Prevents wear and sticking
- Water-repellent
- Excellent adhesion
- Resistant to weather influences
- Excellent corrosion prevention
- Resistant to weak acids and bases
- Directed jetspray

Physical & chemical data

- Base: EP-2 Grease with PTFE
- Colourname:
 - ◊ Beige
 - ◊ beige
- Smell: characteristic
- Surfaces:
 - ◊ Metal to metal connections, Roller bearings, Metal to plastic connections, Sliding bearings, Door hinges, Ball bearings, Springs, Stabilization rubbers, Shock absorbers, Worm wheels
 - ◊ Metal to metal connections Roller bearings Metal to plastic connections Ball bearings Springs Shock absorbers Towing hooks
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Spray rate: 1,51
- Vapour pressure: 3500/20 bar
- Flash point: n.a.
- Relative density: 0.76 g/ml
- Storage stability: 10 years
- Content:
 - ◊ 500 ML
 - ◊ 200 ml

How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The aerosol should have room temperature
- Best processing temperature 10 to 25°C.
- Before use, shake the aerosol.
- Apply the white grease in a thin layer.
- Optimum lubrication is obtained after evaporation of the solvent.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of November 24, 2021 – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim - info-de@european-aerosols.com
European Aerosols B.V., Wolframweg 2, NL-8471 XC Wolvega - info-nl@european-aerosols.com