

MOTIP Ceramic Grease

Ord.-no.: 090307

Technical Information



Assemble ABS brake systems and lambda sensors of the car easily with MOTIP Ceramic Grease. The metal-free ceramic grease is suitable for treating parts that are subject to extremely high loads and/or exposed to very high temperatures. Metal free Ceramic Grease has excellent adhesion.

Quality & properties

- Protects against electrolytic corrosion
- Simplifies the future removal
- Extremely suitable to mount ABS brake systems and lambda sensors
- High thermal stability
- Prevents wear and sticking
- Resistant to chemicals and weather influences
- Directed jetspray
- Resistant to water, salt and weak acids and bases
- Excellent adhesion

Physical & chemical data

- Base: EP-2 Grease with ceramic
- Colourname: White
- Smell: characteristic
- Surfaces: ABS brake systems, Lambda sensors, Brake parts, Exhaust parts, Screwed connections (which are exposed to high temperature), Industrial ovens
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Spray rate: 1,65
- Vapour pressure: 3500/20 bar
- Flash point: n.a. °C
- Relative density: 1.26 g/ml
- Storage stability: 10 years
- Content: 500 ML

How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The aerosol should have room temperature.
- Best processing temperature 10 to 25°C.
- Before use, shake the aerosol.
- Apply ceramic grease. The specific lubrication properties of ceramic grease will be obtained after evaporation of the solvent (approximately 1 minute).

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labeling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of November 24, 2021 – This release replaces all eventually earlier issued versions.