

MOTIP Cut & Drill Lubricant

Ord.-no.: 090407



Technical Information

Prevent overheating of metals in cutting and drilling activities with MOTIP Cut & Drill Lubricant. Cut and Drill Lubricant protects and lubricates the tool and reduces wear of the tool. MOTIP Cut and Drill Lubricant is silicone-free and non-corrosive.

Quality & properties

- · Protects and lubricates the tool
- Reduces wear of the tool
- Silicone-free
- Non-corrosive

Physical & chemical data

Base: Mineral oil

• Colourname: Transparent light brown

• Smell: characteristic

 Surfaces: Cutting, Sawing, Turning, Milling, Drilling

Minimum Working Temperature: 10 °C
Maximum Working Temperature: 25 °C

Spray rate: 1,77

Vapour pressure: 3500/20 bar

Flash point: n.a. °CRelative density: 0.85 g/mlStorage stability: 10 years

Content: 500 ML

How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The aerosol should have room temperature.
- Best processing temperature 10 to 25°C.
- Before use, shake the aerosol.
- Before processing, spray the tool and the material generously.
- The tool and the material must remain moist during the activities.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposa

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version

For any further technical questions call our hotline from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of November 24, 2021 – This release replaces all eventually earlier issued versions.